



1051 Low Ohm Resistance Box

- 0.01Ω to 1MΩ
- High accuracy, low temperature coefficient
- Clear visual indication with colour coded digits
- Ideal for Platinum Resistance Thermometer simulation



Introduction

The 1051 has been developed to meet the need for a wide range low ohms resistance box for general laboratory work and applications in platinum resistance thermometry.

Switch Contacts

Special attention has been given to the problem of reliability of operation. A special multiple gold contact arrangement ensures low contact resistance and continued operation even if a contact should fail.

To prevent misreading or setting, the 1051 has colour coded digits, dividing the settings into mOhms, Ohms, and kOhms.

Specification

Resistance Range:		0.01Ω to 1MΩ in 0.01Ω steps						
RANGE	0.01 Ω	0.1Ω	1Ω	10Ω	100Ω	1kΩ	10kΩ	100kΩ
ACCURACY ±	10%	5%	1%	0.5%	0.1%	0.1%	0.1%	0.1%
MAX CURRENT	1A	1A	1A	0.3A	0.1A	33mA	10mA	3mA
Zero Residual Resistance :		less than 90mΩ						
Residual Resistance Stability:		less than 3 mΩ						
Maximum Voltage:		250V DC						
Power Rating:		1 watt per resistor						
Temperature Coefficient:		100 ppm per °C						
Dimensions:		110 x 75 x 200 mm						
Weight:		0.6 kg						
Optional Extras:		Carrying Case for field/industrial applications. Calibration Certificate traceable to N.P.L./ UKAS						

Ordering Information

Description	Order Code
Low Ohm Resistance Box	1051
Carrying Case	9026
N.P.L. Traceable Calibration Certificate	9161
UKAS Calibration Certificate	9114



Time Electronics Limited,
 Telephone: 01732 355993
 E-Mail: mail@TimeElectronics.co.uk

Botany Industrial Estate, Tonbridge, Kent, TN9 1RH.
 Fax: 01732 770312
 Web Page: www.TimeElectronics.co.uk